

# Index

## Numbers

1403, 21-19

1404, 21-19

## B

BIOS Group

BIOS Setup Control  
Table, 16-2

Diskette Control Table, 16-22

IDE Control Table, 16-20

Network Interface Control  
Table, 16-24

Parallel Port Control  
Table, 16-14

SCSI Control Table, 16-12

Serial Port Control  
Table, 16-16

USB Control Table, 16-18

BIOS Group tables, 16-2

BIOS Setup Control

Group, 16-1

variable values, 16-26

## C

Chassis Information Group  
tables, 5-2

Chassis Information  
Table, 5-2

Event Log Table, 5-17

Firmware Table, 5-23

Intrusion Table, 5-26, 5-29

POST Log Table, 5-15

System BIOS Table, 5-20

UUID Table, 5-14

Variable Values, 5-33

Cluster Group, 20-2

Cluster Table, 20-2

variable values, 20-5

Cost of Ownership Group

COO Cost Event Log  
Table, 18-15

COO Lease Information  
Table, 18-19

COO Maintenance  
Table, 18-25

COO Options Table, 18-23

COO Repair Table, 18-27

COO Schedule Number  
Table, 18-22

COO Service Contract  
Table, 18-13

COO Support Information  
Table, 18-29

Cost of Ownership Group  
(continued)

COO Trouble Ticket  
Table, 18-31

COO Warranty Table, 18-17

Cost of Ownership Table, 18-2

Cost of Ownership  
tables, 18-2

## D

data types

common, A-2

state capabilities, A-3

state settings, A-3, A-4

status, A-4

status probe, A-5

status redundancy, A-5

Device Group

Cache Device Table, 13-12

Generic Device Table, 13-26

Keyboard Device Table, 13-5

Memory Device Mapped  
Address Table, 13-23

Memory Device Table, 13-17

PCI Device Configuration  
Space Table, 13-32

PCI Device Table, 13-29

Pointing Device Table, 13-2

Processor Device Table, 13-7

variable values, 13-35

- L**
- Local Response Agent Group
    - LRA Action Table, 17-5
    - LRA Global Settings, 17-2
    - LRA Global Settings Table, 17-2
    - variable values, 17-7
  - Local Response Agent Group tables, 17-2
- M**
- Memory device correction rate crossed a warning threshold, 21-19
  - Memory device ECC
    - Correctable error count crossed a warning threshold, 21-19
  - Memory Group
    - Physical Memory Tables, 15-2
    - variable values, 15-10, 15-16
  - MIB
    - minor version number, 2-2
  - MIB Major Version Number, 2-2
- O**
- Operating System Group
    - Memory Table, 6-4
    - Operating System Table, 6-2
  - Operating System Memory Table, 6-4
- P**
- Port Group
    - Keyboard Port Table, 12-5
    - Memory Device Port Table, 12-10
    - Monitor Port Table, 12-13
    - Parallel Port Table, 12-19
    - Pointing Port Table, 12-2
    - Processor Port Table, 12-8
    - Serial Port Table, 12-23
    - Small Computer System Interface Port Table, 12-16
    - Universal Serial Bus Port Table, 12-26
    - variable values, 12-29
  - Power Group
    - Amperage Probe Table, 8-12
    - Power Supply Table, 8-4
    - Power Unit Table, 8-2
    - variable values, 8-21
    - Voltage Probe Table, 8-7
  - Power Group tables, 8-2
- R**
- Remote Access Group, 19-2
    - Remote Access Table, 19-2
    - Remote SNMP Trap Table, 19-19
    - Remote User Administration Table, 19-11
    - Remote User Dial-In Configuration Table, 19-27
    - Remote User Dial-Out Table, 19-30
  - Remote Flash BIOS Group
    - variable values, 11-5
  - Remote Flash BIOS Table, 11-2
- S**
- sample SNMP output, B-1
  - Slot Group
    - System Slot Table, 14-2
    - variable values, 14-6
  - SNMP
    - introduction to, 1-11
    - SNMP MIB OIDs, 1-13
    - SNMP security, 1-14
    - SNMP traps, 1-14
  - SNMP basic terminology
    - fields, 1-5, 1-6
    - managed object, 1-4
    - MIB, 1-5
    - SNMP, 1-4
    - variable, 1-5
  - SNMP tables, 1-7
    - example, 1-8
    - reference guide content, 1-9
  - System Resource Group
    - Direct Memory Access Table, 7-16
    - Input/Output Port Table, 7-7
    - Interrupt Table, 7-13
    - Map Table, 7-2
    - Memory Table, 7-10
    - Owner Table, 7-5
    - variable values, 7-20
  - System State Table, 4-2

- systems management
  - software, 3-2
  - build number systems, 3-3
  - description name, 3-3
  - name, 3-2, 3-4
  - preferred protocol, 3-4
  - supported protocol, 3-3
  - version number name, 3-3

## **T**

### Thermal Group

- Cooling Device Table, 9-4
- Cooling Unit Table, 9-2
- Temperature Probe Table, 9-9
- variable values, 9-14

- trap variables, 21-2
  - current status, 21-3
  - data, 21-4
  - message, 21-3
  - previous status, 21-3
  - system, 21-2
  - table index OID, 21-3

- traps, 21-6
  - AC power cord traps, 21-21, 21-22
  - amperage probe traps, 21-13
  - chassis intrusion traps, 21-15
  - cooling device traps, 21-9
  - fan enclosure traps, 21-20
  - memory device traps, 21-19
  - miscellaneous traps, 21-7
  - power supply traps, 21-18
  - redundancy unit traps, 21-16
  - temperature probe traps, 21-8
  - understanding the trap
    - descriptions, 21-4
    - understanding trap severity, 21-6
  - voltage probe traps, 21-11

## **U**

- User Security Table, 10-2

## **V**

- variable names
  - capability, 1-6
  - settings, 1-7
  - state, 1-7
  - status, 1-7

